

HORIZONTAL PLATE & BEAM CLAMPS



The IPH10 horizontal lifting clamps with spring loaded tension have a pretension feature that allows the user to attach the clamps to the material for horizontal lifting and transfer of non-sagging material. These clamps must be used in pairs or more.



The IPBKZ beam clamp is used for lifting, transfer and stacking of H-Beams. An over-center hoist eye allows for the beam flange to remain vertical. This series of clamps can be used in the vertical and horizontal moving, transfer and stacking of different types of structural designs, such as H-Beams, angles, etc., depending on the application desired.



This IPTK series beam clamp is suitable for use as a temporary tackle eye for a beam.



The IPVK drum clamp is for vertical lift and transfer. Automatically locks on drum, and can be used alone or in pairs.



The IPHGZ, IPHGUZ horizontal lifting clamps have a pretension locking feature that allows the user to attach the clamps to the material for horizontal lifting and transfer of sagging and non-sagging material. These clamps may also be used to handle material that will be used in shears, bending and rolling machines or other fabrication equipment. May also be used to move and lift structural shapes such as I-Beams, H-beams etc.



The IPBHZ beam clamp is used for horizontal lifting and transfer of steel beams. The base is slotted to allow the clamps to be used from end of beams as well as from the flange. This series of clamps can be used in the vertical and horizontal moving, transfer and stacking of different types of structural designs, such as H-Beams, angles, etc., depending on the application desired.



The IPSTARTECH11 beam clamp has been specially developed for lifting with the body in vertical position, controlled tilting, transportation and stacking of steel "H" and "I" profiles. By placing the chain guide in the appropriate position, it is easy to switch from lifting to tilting and back again, which shifts the centre of gravity.



The IPU10/A automatically click on to the material as soon as the clamp is placed on the plate. The fact that the safety lock remains in position as the clamp closes precludes hazardous situations. Fastening the IPU10/A clamp in places that are difficult to reach is no problem.

MODEL	WORKING LOAD LIMIT (t)*	IPU10 STOCK NO.	WEIGHT EACH (kg.)	DIMENSIONS (mm)									
				Jaw A	B	C	D	E	F	G	H	J	K
MODEL IPH10													
IPH10	2	2703522	5.5	0-60	117	16	-	22	109	256	110	20	40
IPH10	3	2703523	7.5	0-60	117	20	-	26	109	266	120	20	48
IPH10	6	2703525	13.0	0-60	143	25	-	36	123	320	130	20	48
MODEL IPHGUZ - Fixed Hoisting Eye													
IPHGUZ	1.5	2705455	9.0	0-25	110	232	287	70	139	90	-	20	16
MODEL IPBKZ													
IPBKZ	1.5	2705781	7.0	5-25	62	210	300	70	163	61	50	16	-
MODEL IPBHZ													
IPBHZ	1.5	2705462	6.0	0-25	60	200	255	50	153	73	-	35	28
IPBHZ	3	2705463	10.5	0-40	80	227	325	70	188	112	-	38	32
MODEL IPTK - with Hoisting Eye													
IPTK	2	2700996	6.0	75-190	-	A+80	125	75	-	-	25	-	20
IPTK	5	2700994	11.0	120-350	-	A+195	125	75	-	-	40	-	20
MODEL IPSTARTECH11													
IPSTARTECH11	1.5	2701812	6.6	6-12	140	39	575	110	81	129	54	126	16
DRUM CLAMP - MODEL IPVK													
IPVK	0.5	2700116	1.6	17	26	26	132	29	-	51	-	-	11
CROSBY® IP CLAMP Misc. - MODEL IPU10/A - For vertical transport of plates													
IPU10/A	1	2701628	2.3	0-20	45	138	238	40	128	41	37	-	11