

## STEEL WIRE ROPE RAISE BORE SLING

Steel wire rope sling 2.8 Ton,  
soft eye one end & 38mm  
Expansion shell fitted to other end

Available in 1.8M & 3M configurations



Use: In underground mining where there is a requirement to lift a load in a haulage where there is no lifting point available

Note: The ground conditions will dictate the Safe Working Load, as the sling was tested in ideal circumstances in a test bench

The sling can be used individually or in a cluster dependent on the size of load to be lifted.

### Tested by



Shutterlock Part No: RB R\TYPE20X1200-M24  
Raise Bore Sling 20 Dia x 1.2 M, c/w Exp Shell 1 End  
Soft Eye 1 End, c/w M 24X38 Shell & M24 Studfast  
SWL 2.8 Ton, Fos 6:1

Shutterlock Part No: RB R\TYPE20X1800-M24  
Raise Bore Sling 20 Dia x 1.8 M, c/w Exp Shell 1 End  
Soft Eye 1 End, c/w M 24X38 Shell & M24 Studfast  
SWL 2.8 Ton, Fos 6:1

Shutterlock Part No: RB R\TYPE20X3000-M24  
Raise Bore Sling 20 Dia x 3.0 M, c/w Exp Shell 1 End  
Soft Eye 1 End, c/w M 24X38 Shell & M24 Studfast  
SWL 2.8 Ton, Fos 6:1

